## Technical Data Sheet



# **ACTIV VAD**

# ANTISTATIC DETERGENT, SUPERCONCENTRATED, BIODEGRADABLE

Packaging (It)

25 - 210 - 1000

#### Properties

Alkaline liquid detergent, composed of new generation surfactants, surface tension reducers, designed for use with high pressure cleaning machines..

Its innovative blend of surfactants penetrates and dissolves dirt quickly, making it virtually unnecessary to scrub.

ACTIV VAD produces a reduced level of foam during the wash, not hindering the checking of the degree of cleanliness of the surface, with the consequent savings in time and product. Facilitates rinsing and does not attack any of the vehicle's components.

DILUTION 5% 2,5% 1% light soiling moderate heavy duty soiling



## Technical Data Sheet



# TECHNOLOGY / ADVANTAGES

- Neutralises the harmful effects of hard water and prevents the deposition of salts on clean surfaces
- Quickly penetrates and releases grease, soot, oils, various deposits and stubborn stains
- Economical and multifunctional
- No mechanical action required
- Excellent degreasing capacity
- Biodegradable & non flammable cleaner
- Can be used for general cleaning in the engine room, outside paint work and on the deck

#### **Physical-Chemical Characteristics**

| Physical<br>Condition: | Red Liquid         |
|------------------------|--------------------|
| Odour:                 | Characteristic     |
| <u>рН:</u>             | 12,5 <u>+</u> 0,5  |
| Density at 20°:        | 1,05 - 1,07 (kg/L) |

The data described above are typical values and should not be considered as a specification.

# APPLICATION

### Dilution

Prepare the wash solution with a concentration between 1 and 5%, or adjust the automatic dilution system in the same proportion.

#### Application

Apply by spraying or using a foam tip, starting from the bottom of the surface gradually working upwards. Allow solution to penetrate soil for about 3-5 minutes before washing off thoroughly with high pressure water

#### **Material Compatibility**

It is compatible with most metals, plastics, rubbers, glass and other materials.

## Technical Data Sheet



## HANDLING

#### Storage

Keep in tightly closed original container in a cool place. Keep locked up and out of the reach of children.

#### **Safety Precautions**

Do not mix with other products. In case of contact with eyes, rinse immediately with running water and consult a doctor. Wear suitable gloves and eye/face protection.

#### Attention

- Proper use is the responsibility of the applicator.
- Make sure you are using the most current versions of the Technical Data Sheet and Safety Data Sheet.
- For professional use only. Keep away from children.

#### Chemzy Portugal Lda.

Jardia Business Park - BL 2870-607 Montijo

www.chemzy.pt

**Customer Service and Technical Support** 212 313 516

#### Warranty

The indications given on our labels, information, technical data sheets or manuals, are the result of laboratory tests, or field applications, which have proved to be predominantly significant under normal conditions of application. The results obtained under these conditions have enabled us to define general recommendations, which must be adapted to particular cases. Our responsibility is expressly limited to the supply of carefully controlled products and their proper application when under our control.

Ordering and receiving the products implies acceptance of the guarantee in the terms indicated above, even when the order form or purchase order does not specify or indicates otherwise.

No representative is authorised to assume a supplementary guarantee on our behalf following the sale of our products. Chemicals can cause serious injury. Before use, the Safety Data Sheet should be consulted and its instructions followed to prevent occupational injury.

The purchaser must determine the suitability of the product for the purpose for which it is intended, assuming the duty to check all factors involving its application, such as the characteristics and finish of the materials/surfaces to be treated, environmental conditions, professionalism of the applicator, etc.

It is always recommended to carry out a preliminary test on the surface to be treated. We accept no liability for incorrect use of our products.

Exclusively for professional use. Last revised 09/20